


## colorPol® UV 375 BC5

Spectral range	UV
Wavelength range with <b>contrast &gt; 100 000 : 1</b> <sup>(1)</sup>	362 to 392 nm
Transmittance (uncoated)	> 40 % up to 47 %
Wavelength range with <b>contrast &gt; 10 000 : 1</b> <sup>(1)</sup>	360 to 397 nm
Transmittance (uncoated)	> 40 % up to 48 %
Wavelength range with <b>contrast &gt; 1 000 : 1</b> <sup>(1)</sup>	357 to 403 nm
Transmittance (uncoated)	> 39 % up to 48 %
Filter thickness (laminated) <sup>(2)</sup>	1,7 ± 0,2 mm / 2,0 ± 0,2 mm
Acceptance angle	± 20°
Polarization axis	< 0.5° to edge
Operating temperature	-20 to +80 °C
<sup>(1)</sup> contrast: ratio of parallel to perpendicular transmittance	
<sup>(2)</sup> other thicknesses on request	
Date: 09.02.2010	



**CODIXX AG**

Steinfeldstraße 3  
D-39179 Barleben  
Germany

Phone: +49 39203 963 0  
Fax: +49 39203 963 33  
Email: colorpol@codixx.de  
Internet: www.codixx.de

Version 1.4 – 10/22/2003